

30 & 35SHT

The perfect three-phase inverter for commercial installations



Integrated string fuses
with 3 strings in parallel



Wide input voltage range
Variable system planning



Suitable for outdoor use
Protection against dust and water jets



WLAN Quick install
via MaxLink App



Monitoring Portal
and Service Hotline



Compact dimensions
Low weight

Technical specifications

	30SHT (50) ²	35SHT (50) ²
Input values		
MPPT voltage range	200 V ... 960 V	
MPPT voltage range at nominal power	540 V ... 800 V	
Maximum DC voltage	1,000 V	
Minimum DC voltage for startup	250 V	
Minimum DC voltage for shutdown	200 V	
Maximum DC current	110 A (33A / 33 A / 22 A / 22 A)	
Maximum DC current per string	11 A	
Maximum DC short circuit current	140 A (42 A / 42 A / 28 A / 28 A)	
Number of MPP trackers	4	
Maximum PV output per MPPT	MPPT 1 & 2: 22,500 W / MPPT 3 & 4: 15,000 W	
Number of string connections	10 (3/3/2/2)	
Connection type	Amphenol H4 (type MC4)	
Output values		
Rated output power	30,000 W	35,000 W
Maximum apparent power	30,000 VA	35,000 VA
Maximum AC current	3* 83 A	3* 92 A
Mains nominal voltage	400 V (3 L + N + PE)	
Mains voltage range ¹	277 V ... 520 V	
Mains frequency ¹	50 Hz / 60 Hz	
Mains frequency range	45 Hz ... 55 Hz / 55 Hz ... 65 Hz	
Power factor cos (φ)	Adjustable from 0.8 overexcited 0.8 underexcited	
Distortion factor at rated output power	< 3 %	
Power input at night	< 1 W	
Connection type	Connector	
Efficiency		
Maximum efficiency	98.3 %	
Euro efficiency	98.0 %	
Ambient conditions		
Protection class	IP65	
Ambient temperature range	- 25 °C ... + 60 °C	
Relative humidity	0 % ... 100 % (not condensing)	
Cooling	With fan	
Maximum operating height above sea level	4,000 m (> 2,000 m derating)	
Audible noise emissions	< 65 dB(A) @ 1 m	
Equipment		
Display	App over WLAN connection + LED	
Inverter topology	Transformerless	
DC disconnecter	Integrated	
DC polarity inversion protection	Integrated	
Residual current monitoring unit (RCMU)	Integrated	
Mains protection interface	Integrated	
Protection class (IEC 62109-1)	I	
Overvoltage category (IEC 62109-1)	AC: III / DC: II	
AC/DC surge arrester	Type 2 / Type 1 + 2	
Standard & guidelines		
EMV	EN61000-6-2, EN61000-6-4	
Grid connection	EN50549-1, EN50549-2, VDE-AR-N 4110, VDE-AR-N 4105, IEC61727, IEC62116, VDE 0126-1-1, CEI 0-21	
Device safety	IEC62109-1, IEC62109-2	
Interfaces		
Data communication	WiFi, RS485	
Weight & dimensions		
Weight	83 kg	
Dimensions (W x H x D)	855 mm x 710 mm x 285 mm	
Warranty		
Standard warranty	5 years / optional 10 years	



The quality management system of SOLARMAX GmbH is certified according to ISO 9001:2015.

- 1) Output voltage and frequency can vary depending on country setting and grid code.
- 2) Choked 50SHT, choking must be carried out by the installer.

All rights, modifications and errors excepted.

DOWNLOAD APP NOW
and start directly!



Until
10 YEARS
Warranty